

## Videobar HY200



## Specifications

<b>Name</b>	Videobar
<b>Model</b>	HY200
<b>Integrated Design</b>	Camera, Microphone, Speaker
<b>Camera</b>	
<b>Image Sensor</b>	1/2.8 inch High Quality 4K CMOS Sensor
<b>Effective Pixels</b>	8MP, 16:9
<b>Video Output</b>	Maximum output 4K image
<b>Digital Zoom</b>	5X
<b>AI Intelligent Framing</b>	Face Detection & Sound Source Localization & Voice Tracking
<b>Optical Lens</b>	116°(D) / 107.2°(H) / 74.1°(V)
<b>Video Resolution</b>	4K/30 and below
<b>PTZ</b>	EPTZ
<b>DNR</b>	2D&3D
<b>BLC</b>	On/off
<b>SNR</b>	≥55dB
<b>Operation System</b>	Windows 7, Windows10, Mac os 10.10 or higher systems
<b>Audio</b>	
<b>Microphone</b>	6 Digital Array Microphones

Pickup Range	10m
Audio Processing	AEC & AGC & ANS & Sound Source Localization
Speaker	2*7W
<b>Interface</b>	
USB Interface	1*USB3.0, Type B
Audio Interface	1*3.5mm linear input
Power Interface	HEC3800 outlet(DC12V)
Bracket	Wall Mounting
<b>Controller</b>	
Remote Control	Infrared Remote Control

**Videobar HY200 Dimension (unit: mm)**

